



HYDE F15 TUNING GUIDE

Wind Speed	1-6 <u>Knts</u>	7-11Knts	12-16knts	17-21knts	22+knts
Mast Rake	24'9 (7540)	24'10 (7570)	24'9 (7540)	24'8 (7518)	24'8 (7518)
Rig Tension	26	28	26	24	24
Mast Ram from Neutral	Forward 20mm	Forward 10mm	Neutral	Aft 5mm	Aft 10mm
Kicker	Slack	Tack Up Slack/little on	Straight main leech	Max	Slight ease from max
Outhaul	Tight	Eased 10mm	Tight	Max	Max
Cunningham	No	No	No - take up slack	Medium	Tight
Jib Luff	Wrinkles	Very Small Wrinkles	Just take out Wrinkles	No Wrinkles	Tight
Jib Car position Back of boat to centre block	2950	3030	3030	3030	3000
Jib track from centreline	410	410	410	410	410
Spreader Deflection	>26 stone 200mm	26 stone + 190mm			
Spreader Length	>26 stone 430mm	26 Stone + 430mm			
Mast Heel Position	Is 93mm from Centre of first keel bolt to aft of mast heel bolt. Assumes Keel position is standard.				

Mast Rake is measured by pull the tape measure up until you read 6248 at the top of the bottom black band then swung to the transom